







# CERAMIC METAL HALIDE PRODUCT LISTING



**T**  T6  
Dia. = 0.8" (20mm)  
MOL = 3.9" (99mm)  
LCL = 2.2" (56mm)  
Base = G12

**V**  V  
Dia. = 0.6" (15mm)  
MOL = 3.3" (85mm)  
LCL = 2.0" (51mm)  
Base = G8.5

**RI**  MH-DE T6  
Dia. = 20mm  
Insertion Length = 117.6mm  
Contact to Contact = 114.2mm  
Base = RSC (R7s)

**SI**  MH-DE T7  
Dia. = 23mm  
Insertion Length = 135.4mm  
Contact to Contact = 132.0mm  
Base = RSC (R7s)

## Open Rated Ceramic Metal Halide LAMPS ANSI Type-E

Watts	Lamp Description	Product No.	ANSI Code	Initial Lumens	LPW	Rated Life (hrs)	CCT	CRI	Finish	Oper. Pos.	Fig.	Case Qty
20	CMH 20W/U/T4/UVS/942	15648	C156/E	1800	90	9000	4200K	90	Clear	U	V	12
20	CHM 20W/U/T4/UVS/830	87631	C156/E	1800	90	9000	3000K	80	Clear	U	V	12
20	CHM 20W/U/T6/UVS/830	46874	C156/E	1800	90	10000	3000K	80	Clear	U	T	12
20	CHM 20W/U/T6/UVS/942	83546	C156/E	1650	83	10000	4200K	90	Clear	U	T	12
35	CHM 35W/U/T4/UVS/942	17798	C130/E	3300	94	12000	4200K	90	Clear	U	V	12
35	CHM 35W/U/T6/UVS/942	50417	C130/E	3300	94	12000	4200K	90	Clear	U	T	12
35	CHM-DE 35W/U/T6/UVS/942	23576	C130/E	3300	94	15000	4200K	90	Clear	U	RI	12
35	CHM 35W/U/T4/UVS/830	12497	C130/E	3400	97	12000	3000K	80	Clear	U	V	12
35	CHM 35W/U/T6/UVS/830	20784	C130/E	3400	97	12000	3000K	80	Clear	U	T	12
70	CHM 70W/U/T4/UVS/942	24957	C139/E	6600	94	12000	4200K	90	Clear	U	V	12
70	CHM 70W/U/T4/UVS/830	87965	C139/E	7000	100	12000	3000K	80	Clear	U	V	12
70	CHM 70W/U/T6/UVS/942	64302	C139/E	6600	94	12000	4200K	90	Clear	U	T	12
70	CHM 70W/U/T6/UVS/830	87456	C139/E	7000	100	12000	3000K	80	Clear	U	T	12
70	CHM-DE 70W/U/T6/UVS/942	23756	C139/E	6600	94	15000	4200K	90	Clear	U	RI	12
70	CHM-DE 70W/U/T6/UVS/830	54124	C139/E	7000	100	15000	3000K	80	Clear	U	RI	12
100	CHM 100W/U/T6/UVS/942	27452	C191/E	9000	90	12000	4200K	90	Clear	U	T	12
100	CHM 100W/U/T6/UVS/830	32745	C191/E	9500	95	12000	3000K	80	Clear	U	T	12
150	CHM 150W/U/T6/UVS/830	35786	C142/E	15000	100	12000	3000K	80	Clear	U	T	12
150	CHM 150W/U/T6/UVS/942	41564	C142/E	13500	90	12000	4200K	90	Clear	U	T	12
150	CHM-DE 150W/U/T7/UVS/942	78538	C142/E	12500	83	15000	4200K	90	Clear	U	SI	12
150	CHM-DE 150W/U/T7/UVS/830	87745	C142/E	1400	93	15000	3000K	80	Clear	U	SI	12



**Call 800-965-2677**

**Fax 800-865-2677**

**email: [custserve@HIDirect.com](mailto:custserve@HIDirect.com)**

**HIDirect.com**